## APPLICATION TO ERECT MONUMENT/MARKER GREENWOOD CEMETERY - NEWCASTLE, WYOMING

Name and address of applicant:		Date:	
Name, grave description of	and placement of monum	ent/marker:	
Signature of applicant: _			
	<u>Permit</u>		
applicant to lay or erect foregoing Application, su	a monument/marker of the bject to the regulations a	Newcastle hereby authorizes the above named ne type and at the location described in the nd restrictions regarding the construction of Ordinances, Section 14-35.	
DATED THIS	day of	20	
	CITY OF NEV	VCASTLE	
CITY COMMISSIONER		CITY CLERK	

## NEWCASTLE CITY ORDINANCES SECTION 14-35

Markers and monuments laid or erected in the cemetery shall comply with the following specifications and requirements;

(a) Only one marker can be permitted for any one burial space. As a general rule, only one monument can be permitted for any one family group of lots in order to avoid an overcrowded appearance.

(b) Any stone exceeding any one or more of the following dimensions shall be classified as a monument: namely, one foot in height, two feet in length or one foot in thickness. Any stone not exceeding any of the above dimensions shall be classified as a marker.

- (c) No monuments or markers made of material other than granite, marble, standard bronze or finished concrete with bronze marker will be allowed in the cemetery.
  - (d) All stone work shall have the surface next to the foundation squared so as to allow full bearing on the foundation.
- (e) All monument foundations shall be built so as to provide a border five inches in width around the bottom of the base of the monument level with the existing ground level and shall be adequate to permanently support the monument in true position.
- (f) After the foundation for any monument has been set sufficiently, as determined by the City, the monument shall be installed on the foundation by a representative of the manufacturer of the particular monument.
- (g) Markers for use in marking graves in baby plots shall be of the surface type and must not exceed one foot in length or six inches in width and shall not be more than six inches thick.
- (h) All markers shall be set in a concrete foundation which will provide a five inch concrete border around the marker, such concrete border to be flush with the level of the ground.